US009644398B1

(12) **United States Patent**
Cheng et al.

(10) **Patent No.: US 9,644,398 B1**
(45) **Date of Patent: May 9, 2017**

(54) **INTELLIGENT DOOR LOCK SYSTEM WITH A HAPTIC DEVICE**

(71) Applicant: **August Home, Inc.**, San Francisco, CA (US)

(72) Inventors: **Shih Yu Thomas Cheng**, Union City, CA (US); **Jason Johnson**, San Francisco, CA (US); **Christopher Kim**, San Francisco, CA (US); **Joseph Aranda**, San Francisco, CA (US)

(73) Assignee: **August Home, Inc.**, San Francisco, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 290 days.

(21) Appl. No.: **14/205,973**

(22) Filed: **Mar. 12, 2014**

Related U.S. Application Data

(60) Provisional application No. 61/800,937, filed on Mar. 15, 2013, provisional application No. 61/801,236, filed on Mar. 15, 2013, provisional application No. 61/801,294, filed on Mar. 15, 2013, provisional application No. 61/801,335, filed on Mar. 15, 2013.

(51) **Int. Cl.**

E05B 39/00	(2006.01)
E05B 47/00	(2006.01)
G07C 9/00	(2006.01)

(52) **U.S. Cl.**
CPC ***E05B 39/00*** (2013.01); ***E05B 47/0001*** (2013.01); ***G07C 9/00007*** (2013.01)

(58) **Field of Classification Search**
None
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,680,177	A	6/1954	Rosenthal	
3,898,976	A *	8/1975	Coffman, Jr.	F24F 6/12 126/113
5,306,407	A	4/1994	Hauzer et al.	
5,407,035	A	4/1995	Cole et al.	
5,594,430	A	1/1997	Cutter et al.	
5,695,048	A	12/1997	Tseng	
6,196,936	B1	3/2001	Meckel	
6,323,846	B1	11/2001	Westerman et al.	
6,418,764	B1 *	7/2002	Lerchner	E05B 47/0012 70/279.1

(Continued)

FOREIGN PATENT DOCUMENTS

CA	2676196 A1	7/2008
CA	2834964	8/2012

(Continued)

Primary Examiner — Daniell L Negron
(74) *Attorney, Agent, or Firm* — Paul Davis

(57) **ABSTRACT**

An intelligent door lock system includes a position sensing device configured to be coupled to a drive shaft of a lock device. The position sensing device senses position of the drive shaft to assist in locking and unlocking a lock of a lock device. A circuit is coupled to an engine with a memory. A haptic device is coupled to the circuit. The haptic device provides a visual indication that the lock has reached a final position. A device converts energy into mechanical energy and is coupled to the drive shaft. The positioning sensing device, the circuit, the position sensing device and the device that converts energy operate to rotate the drive shaft to lock and unlock the lock device.

26 Claims, 40 Drawing Sheets